

GenSet



MG 115 SS-P



GEN SET S.p.a.

Via Stazione,5 - 27030 Villanova D' Ardenghi (Pavia) Italy

Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244

E-mail: genset@genset.it - internet: [//www.genset.it](http://www.genset.it)

MG 115 SS-P

SUPER SILENCED THREE-PHASE POWER GENERATOR / OUTPUT POWER
110 KVA THREE-PHASE AND 37 KVA SINGLE-PHASE / DIESEL ENGINE 1500 RPM

| | |
|--|---|
| Gen Set Features | <ul style="list-style-type: none"> + Controller (DSE 6120) with digital display for full monitoring of generator parameters: 3-phase generator voltage, 3-phase mains voltage, battery voltage, ammeter, frequency, hour meter, oil pressure, engine temperature, fuel level, fail to start; with auto engine protection shutdown system in case of: <ul style="list-style-type: none"> - fail to start - emergency stop - low oil pressure - low fuel level - high coolant temperature - oil pressure sender open circuit - over/under voltage - over/under frequency - open door + Adjustable Earth leakage Relay + 4 poles main Circuit Breaker + Three-phase output terminal board + Emergency STOP button + Set mounted distribution board with: <ul style="list-style-type: none"> - 1x32A, 400V - 50Hz three-phase EEC socket protected by Circuit Breaker - 1x16A, 400V - 50Hz three-phase EEC socket protected by Circuit Breaker - 1x32A, 230V - 50Hz single-phase EEC socket protected by Circuit Breaker - 2x16A, 230V - 50Hz single-phase EEC socket protected by Circuit Breakers + Automatic Voltage Regulator + Electronic frequency regulator + Manual oil sump pump + Battery switch + Central lifting eye + Fork-lift pockets + Bunded base to retain all liquids + Remote control terminal board + ATS terminal board + Preset for A.M.F. operation + Fuel/Water separator |
| Gen Set Options (available as factory options) | <ul style="list-style-type: none"> + 60 Hz version + Versions with different voltages + Engine water heaters powered by mains 230 V - 50 Hz + Spark arrester muffler + Long run fuel tank (24h) complete with bunded base + Separate tank facility c/w quick release coupling |
| Accessories on Request | <ul style="list-style-type: none"> + Two-wheels site tow undercarriage (GRT2W) + Remote Start/Stop kit by cable (20/50 m) + Auto Transfer Switch (ATS) panel complete with battery charger for auto-start operation |
| Noise Level | <ul style="list-style-type: none"> + Lwa 94 (69 dB a 7 m) |
| AC Generator 50 Hz | <ul style="list-style-type: none"> + Type: synchronous + Three-phase power (stand by): 110 kVA - 400 V + Three-phase power (prime): 100 kVA - 400 V + Single-phase power (max.): 37 kVA - 230 V + Power Factor: cos ϕ 0,8 |
| Diesel Engine 1500 rpm | <ul style="list-style-type: none"> + Type: Perkins 1104C-44TAG2 - turbocharged - 4 cyl. 133 HP (98 kWm) - 4400 cm³ + Fuel: diesel + Cooling system: water + Starting system: electric + Fuel tank capacity: 200 l + Fuel consumption @ 75%: 17,1 l/h |
| Other Features | <ul style="list-style-type: none"> + Insulation Class: H + Ambient temperature: 40 °C + Altitude: 1000 mt + Mechanical Protection: IP 23 + Dimensions (L x W x H): 3002 x 1150 x 1767 mm + Dry weight: 2009 kg + Total weight: 2335 kg |

Generator set in designed to operate in ambient temperature up to 40 °C and 1000 mt altitude - For higher values of temperature and altitude please consult factory to check available power.

Specifications and pictures introduced here are not contractual and are subjected to change without prior notice.